

Managed by Fermi Research Alliance, LLC for the U.S. Department of Energy Office of Science

# **POMS** project

Anna Mazzacane February 02, 2018

### In these slides

- ➤I will give an overview of POMS
- ➤I will show some of the many features implemented in POMS



### **POMS**


> The Production Operations Management Service (POMS) is a project to design a service which assists

the production teams and the analysis groups of the experiments in their scientific

computational work.

> POMS provides a web interface to:

- Submit batch jobs
- Monitor job submissions and files delivery
- Recover failed jobs
- Debug failures
- Keep track of configurations used



### What it is needed to use POMS

➤ The production instance of POMS is at <a href="https://pomsgpvm01.fnal.gov/poms/">https://pomsgpvm01.fnal.gov/poms/</a>



- Use services account to login
- Need an experiment affiliation and computing permissions to submit jobs





### **How To Interface To POMS**

➤ First important step is how to translate the experimental workflow of a Monte Carlo production or DATA processing into POMS



# Experimental Workflow - Set Of Stages/Steps





### **Workflow variations**

### **Example**


(Gen+G4+Detsim) + Reco + Mergeana





# **Experimental Workflow into POMS**

- Experimental workflow = POMS campaign
- > A stage in the experimental workflow = POMS campaign stage





# **POMS Campaign Stages**

### Campaign Stages ?





Mark Campaigns Active/Inactive

**Tag/untag Campaigns** 


**Hold/Release Campaign Submission** 

**Show ALL Campaigns Statistics** 

Select All	Name	Active \$	Tags \$	Hold By \$	Creator >	Created \$
	6GeV		dune_mcc9		mazzacan	
	mcc9_reco_protoDune_beam_cosmics_p6GeV	No	dune_mcc9		mazzacan	2017-04-30 08:14:24
	mcc9_gen_G4_detsim_protoDune_beam_cosmics_p6GeV	No	dune_mcc9		mazzacan	2017-04-30 08:13:44
	mcc9_mergeana_protoDune_beam_cosmics_p6GeV	No	dune_mcc9		mazzacan	2017-04-30 08:15:05



# **POMS Campaign Stages Stats**





Jobs in 62.0 days ending 2017-06-30 00:00										
Campaign Stage 🔞		Total Ac		Active Jobs		Completed			Stats	
Name	All	Idle 🛭	Running 🕝	Held 🚱	Total 🚱	Not Located @	Located @	Removed 🚱	%Efficiency @	Pending 🕝
mcc9_mergeana_protoDune_beam_cosmics_p4GeV	206	0	0	0	206	0	206	0	64	0
mcc9_reco_protoDune_beam_cosmics_p4GeV	415	0	0	0	415	0	415	0	110	0
mcc9_gen_G4_detsim_protoDune_beam_cosmics_p4GeV	407	0	0	0	407	0	407	0	58	0




# **Campaign Stage Info**

Campaign Stage Info @ Campaign Stage mcc9\_gen\_G4\_detsim\_protoDune\_beam\_cosmics\_p3GeV



Total	Active Campaign Jobs			Jobs in 278.2 days	ending 2018-02-02	Stats			
All 🕝	Idle 🕝	Running @	Held 🚱	Total Completed ②	Not Located ②	Located ②	Removed ②	%Efficiency ②	Pending ②
405	o V	0	0	405	0	405	0	63	0





# Campaign Stage Info (cont'd)

#### Campaign

Name: mcc9 gen G4 detsim protoDune beam cosmics p3GeV

**Experiment**: dune Dataset: none

Software Version: v06 33 00 01

VO Role: Production cs\_split\_type: none

cs\_split\_dimensions: None

cs\_last\_split: None

**I** Reset

Active: False

Created: 2017-04-29 20:36:56.229675-05:00

**Creator**: mazzacan **Updated**: None **Updater**: mazzacan

#### Job Type

Name: mcc9\_protodune\_detsim\_3GeV

Launch Script: /dune/app/home/dunepro/anna/MCC9/mcc9\_SubmissionScriptNew.sh

**Definition Parameters:** 

['ProtoDUNE\_beam\_3GeV\_cosmics\_3ms.xml', ' ']

['detsim', ' ']]

Input Files Per Job: 0 Output Files Per Job: 0 **Output File Patterns: %.root** 

**Creator**: mazzacan

Created: 2017-04-29 20:33:16.509874-05:00

**Updater**: mazzacan **Updated:** None

#### **Launch Template**

Name: mcc9 protodune

**Experiment: dune** 

Launch Host: dunegpvm01.fnal.gov

Launch Account: dunepro

Launch Setup: export X509 USER PROXY=/opt/dunepro/dunepro.Production.proxy; source

/cvmfs/dune.opensciencegrid.org/products/dune/setup\_dune.sh; setup\_dunetpc v06\_33\_00\_01 -q\_e14:prof

Creator: mazzacan

Created: 2017-04-24 10:45:18.216718-05:00

Updater: mazzacan

Updated: 2017-04-26 12:43:23.738891-05:00



# **Fifemon Monitoring**

Campaign stage profiling






# **Troubleshooting**

Anna Mazzacane

dune

production \$





# **Configure POMS**


- ➤ Two configuration models implemented into POMS:
  - Through a submission script that takes all configurations needed for the job submission and data handling


- Through a configuration file that takes all info needed for the job submission and data handling

**Highly recommended** 




# **Create POMS Campaign Stage**







### **Schedule A Submission**





### **POMS Online Documentation**

#### Job

An individual batch-system job, part of a given Task's job submission, which associated with a Campaign. POMS ignores jobs which are not part of a Campaign. Jobs are considered to be in one of 5 high level states:

- Idle -- The job is waiting to be scheduled somewhere by the batch system
- Running -- The job has been started by the batch system, and is still running
- · Completed -- the job has finished running
- Held -- the batch system has stopped the job for some reason (using too much memory, etc)
- Located -- the job was not only completed, but its output files have locations in the data handling system.

where the first 4 are the usual states are defined by Condor, and the fifth is peculiar to POMS. Within the Running state, there may be more details logged; i.e. "Running: running user executable", "Running: copying in files", etc. where these can be determined from the ifdh joblogs.

#### Service

A system that we depend on to run jobs, whose status is in some way determinable.

#### Job Type

(Task Definition/Campaign (layer) Definition)

All the info you need to run a particular category of job -- i.e. "how do I launch a NOvA montecarlo job" or "how do I launch a Minerva calibration keepup job". This is filled in with information from a given Campaign to know how to run a submit a given Task.

#### Submission

(Task)

A specific multi-job launch. It has a specific command line used to launch it, and it may have output files for whose appearance we await in the data handling system before we declare the task complete. It has states defined in terms of the jobs it generates as follows:

- . Idle -- all of its jobs are Idle
- Running -- one or more of its jobs are Running
- . Completed -- all of its jobs are Completed or Declared
- . Located -- all of its jobs are Located

If another Submission in (another Campaign Layer) needs the output of this one to be launched, it must wait for this task to be in state "Located" before launching; or if the Submissions are generated with a Draining dataset definition, one waits for the previous task for this Campaign to complete before launching another.



### References

POMS redmine project:

https://cdcvs.fnal.gov/redmine/projects/poms/

POMS team mailing list:

poms\_team@fnal.gov

POMS production instance of POMS:

https://pomsgpvm01.fnal.gov/poms/

Marc Mengel's presentation at FIFE workshop 2016:


https://indico.fnal.gov/getFile.py/access?contribId=8&resId=0&materiaIId=slide s&confId=12120



# **Thank You**



# **Backup Slides**







Managed by Fermi Research Alliance, LLC for the U.S. Department of Energy Office of Science

# SBND, ICARUS and POMS Update

Anna Mazzacane February 14, 2018

### **Overview**

- ➤ Last time I did an overview of POMS and showed some of the many features implemented in POMS
- ➤ Since then POMS has implemented a workflow example that doesn't use project.py, but allows to go through all the production steps using the FIFE toolkit.
- ➤ SBND and ICARUS can tune this workflow in order to meet the experiment needs for MC production
- ➤In this slides, I will show:
  - How to configure POMS
  - Workflow example for SBND
  - ➢ Issues found and solved NOT depending on POMS
  - Existing documentation
- > Q&A



# **How To Configure POMS**

- ➤ Last time I mentioned there are two configuration models to interface to POMS:
  - Through a submission script that takes all configurations needed for the job submission and data handling
  - Through a configuration file that handles all info needed for the job submission and data handling

**Highly recommended** 


- Both are passed to POMS through the web interface.
- Future plans will allow users to also interface to POMS client and launch jobs through a command line and have POMS tracking, debugging and monitoring them.



# **How To Configure POMS – Step by Step**

- ➤ I will show step by step how to configure POMS for a general MC production workflow using:
- A configuration file to interface with POMS
- ➤ It's a two steps configuration:
- Edit the configuration file
- Create the POMS Campaign stages

### ➤ Example of SBND worflow tested:





# **How To Configure POMS – step 1**

- 1. Edit the configuration file:
- Example: /sbnd/app/home/poms\_test/cfg/sbnd\_launch.cfg



# **Example of Configuration File**

#### # demo config

```
[global]
group = sbnd
```

experiment = sbnd
wrapper = file:///\${FIFE UTILS DIR}/libexec/fife wrap

version =  $v06_48_00_MCC$ 

quals = e14:prof fclfile = override\_me.

fclbasename=gen

#### [env\_pass]

IFDH\_DEBUG = 1

SAM\_EXPERIMENT=%(experiment)s SAM\_GROUP =%(group)s SAM\_STATION =%(experiment)s

#### [submit]

G = %(group)s

N = 5

#dataset = %(dataset)s -- will override this on processing stages resource-provides = usage model=OPPORTUNISTIC,DEDICATED,OFFSITE

generate-email-summary = True expected-lifetime = 3h #disk = 10GB memory = 2000MB



# **Example of Configuration File (cont'd)**

```
[job_setup]
debug
           = True
find setups = True
            = /cvmfs/sbnd.opensciencegrid.org/products/sbnd/setup sbnd.sh
source 1
setup 1
            = sbndcode %(version)s -q %(quals)s
            = True -- may override this on processing stages
#multifile
#getconfig = False
#ifdh art
            = False
[sam consumer]
limit
               = %(version)s
appvers
[executable]
         = lar
name
arg 1
         = -C
arg 2
         = %(fclfile)s
arg 3
         = -0
arg 4
         = %(basename)s.root
arg 5
         = -s
#arg 6
         = input filename -- will be added by multifile loop...
[job output]
                 = %(basename)s.root
addoutput
                 = unique
rename
                 = /pnfs/sbnd/scratch/sbndpro/poms test/
dest
declare metadata = True
metadata extractor=sam metadata dumper
# add to dataset = poms task -- override this on on the gen stage(s)
add location
                  =True
```



# **How To Configure POMS – step 2**

- 1. Create POMS Campaign Stages:
- Examples: sbnd\_gen\_test, sbnd\_g4\_test, sbnd\_detsim\_test, sbnd\_reco\_test, sbnd\_anatree\_test



# **Create POMS Campaign Stages – Login**


Log into POMS
 https://pomsgpvm01.fnal.gov/poms/



- Use services account to login
- Need an experiment affiliation and computing permissions to submit jobs – Ask your experiment production coordinator




# **Create POMS Campaign Stages – Home**






# **Create POMS Campaign Stages – Compose**






# **Create POMS Campaign Stages – Compose**



➤ You can Add, Edit, Clone and Delete




# **Create POMS Campaign Stages – Clone**





# **Create POMS Campaign Stages – Clone**


- Change the Name
- Overrides Parameter of the configuration file (if needed)
- Create a dependency (for example, g4 stage depends on gen stage)
- Choose the Launch Template and Job Type from the drop down menu
- Click Clone








# Create POMS Campaign Stages – Run






# **Create POMS Campaign Stages – Run**






# **Create POMS Campaign Stages – Run**







# Create POMS Campaign Stages – Run




# Create POMS Campaign Stages – Run



## Create POMS Campaign Stages – Schedule




## **Create POMS Campaign Stages – Schedule**






# **Create POMS Campaign Stages – Schedule**






We successfully ran the following workflow for SBND





- ➤ Each stage of the workflow takes a SAM dataset input with the output files of the previous stage
- Each stage starts automatically when the previous one is finished
































Anna






# Found Issues and Solutions Not Depending on POMS

- We had to solve the following issues that not depends on POMS:
  - Missing library for the g4 stage like libXmu.so
     Hooked them up with the NOvA cvmfs lib area.
     Still saw failures in some offsite nodes, so ran the g4 stage onsite
    - Suggested solution: check which libraries you really need
  - Art's "SAM metadata dumper" can generate metadata keys that aren't valid for SAM
    - Added code to filter them out.
    - Suggested solution: filter the "SAM compliant ones" and drop the rest




#### **Get Help from POMS Team**






#### **Get Help from POMS Team**





#### **Existing Documentation**





# **Thank You**



# **Backup Slides**

